

# DP-6200

**Yamato**

## Bench/Receiving Scale



An excellent, easy to use, digital scale for general purpose weighing and accurate checkweighing. The -6200's large, rotating and tilting display makes it easy to read from any angle or distance.

### Features

- Large LCD Display with Annunciators
- Over/Under Indicator
- Large Stainless Steel Platform
- Push Button Tare
- Battery Operation
- Adjustable Auto Shut-off
- Splashproof (when battery operated and AC jack sealed)
- Legal for Trade
- Tilting and Rotating Indicator
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms



*Reliability you can trust*

## Features

- Large LCD Display with Annunciators
- Over/Under Indicator
- Large Stainless Steel Platform
- Push Button Tare
- Battery Operation
- Adjustable Auto Shut-off
- Splashproof (When battery operated and AC jack sealed)
- Legal for Trade
- Tilting and Rotating Indicator
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms

## Options

- AC Adaptor (not washdown)
- Rechargeable battery pack (Not legal for trade)
- RS-232C
- Printer

## Specifications

Accuracy Class	Class III, 3000 Divisions		
C of C	03-002		
Model	DP-6200	DP-6200C	DP-6200Z*
Capacity and Divisions	60 lb x 0.02 lb (30 kg x 0.01 kg) 150 lb x 0.05 lb (60 kg x 0.02 kg) 300 lb x 0.1 lb (150 kg x 0.05 kg)	960 oz x 0.5 oz (30 kg x 0.01 kg) 2400 oz x 1 oz (60 kg x 0.02 kg) 4800 oz x 2 oz (150 kg x 0.05 kg)	60 lb x 0.5 oz (30 kg x 0.01 kg) 150 lb x 1 oz (60 kg x 0.02 kg) 300 lb x 2 oz (150 kg x 0.05 kg)
Weighing System	Strain gauge load cell		
Platform	13.8" x 19.7" stainless steel (350 mm x 500 mm)		
Display	LED: 5 digits plus annunciators Character size: 0.9" x 0.5" (23 mm x 12 mm)		
Power	6 "D" batteries, optional AC adaptor (not washdown) Rechargeable battery pack (optional)		
Battery Life	600 hours of continuous use with alkaline batteries		
Operating Temperatures	23° F ~ 95° F (-5° C ~ 35° C)		

C= continuous ounce

\*Z= lb-oz, not legal for trade