



# EM Stuffers

Model	Overall Height	Height to Horn	Knee Switch Height	Base Width	Base Depth	Lid Swing Radius	Capacity Litres	Capacity Lbs.
EM-20	43.7"	41.5"	19.7"	16.1"	18.5"	15.6"	20	45
EM-30	47.4"	45.3"	21.7"	18.5"	19.7"	17.3"	30	65
EM-55	51.2"	49.2"	22.4"	21.3"	21.3"	21.3"	55	115



## FEATURES & BENEFITS

- ALL STAINLESS CONSTRUCTION** For Durable Long Life
- STAINLESS STEEL LID & PISTON (Optional on EM-20 & EM-30)** For USDA Approved Facilities
- SIDE MOUNTED KNEE SWITCH** For More Comfortable Operation & Less Knee Strain
- POWERFUL MOTOR** For Faster Stuffing with Stiff Products
- VARIABLE SPEED WITH BUILT IN PRESSURE GAUGE** For Precise Product Control & Power (fig. 1)
- ENCLOSED OIL RESERVOIR** Eliminates Spills while Moving
- THREE STUFFING HORNS INCLUDED** For Maximum Flexibility (Choose from 10, 12, 15, 20, 25, 30 or 40 mm)
- WATER TIGHT CONSTRUCTION** For Carefree Hose-Down Cleaning
- AUTO PISTON DECOMPRESSION** For Less Overstuffing & Bleed-off when Knee Switch is Released
- REMOVABLE PISTON & SWING-OUT LID** For Easy Cleaning (fig. 2)
- SMOOTH PRODUCT DISCHARGE PATH** Eliminates Clogging & Product Discoloration
- KNEE SWITCH "AUTO-ON"** For Noise Free Idle Time (3 phase only)

### OPTIONS:

- MANUAL PORTION CONTROL HEAD** For Precise Filling of Bags & Casings
- ANTI-TILT TROLLEY & CASTORS** For Safe, Stable, Easy, Strain-Free Moving (fig. 3)
- DEPOSITING "L" TUBE with FLAP VALVE** For Quick, Accurate, Drip-less Filing of Liquid Products



Manual Portion Control Head



Depositing Tube



(fig. 1)



(fig. 2)



(fig. 3)

### Technical Data

Motors:  
 3 Phase, 220V, 60Hz  
 1 Phase, 220V, 60Hz  
 1 Phase, 110V, 60Hz  
 Net Weight:

### Model

HP / Amps  
 HP / Amps  
 HP / Amps  
 LBS.

### EM-20

1.25 / 4.5  
 1.50 / 10.5  
 1.50 / 21.0  
 198

### EM-30

1.75 / 5.8  
 2.50 / 11.5  
 2.00 / 26.0  
 295

### EM-55

2.25 / 7.4  
 2.50 / 11.5  
 2.00 / 26.0  
 506



411 Eichelberger Street  
 St. Louis, MO 63111  
 (877) 677-7761  
 Fax (314) 353-6655

Mainca USA Inc. reserves the right to alter any specification without prior notice.



Mainca USA Headquarters  
 St. Louis, Missouri USA



Mainca World Headquarters  
 Barcelona, SPAIN